

DAMASCATO

NATURAL OXIDES BASED DECORATIVE FINISHING
WITH *NUAGE* EFFECT

PRODUCT PROPERTIES

DAMASCATO is a decorative product made of high quality acrylic resins in watery emulsion, natural pigments and special additives that grant to the product the following characteristics:

GOOD TRANSPIRABILITY - GOOD WASHABILITY RESISTANCE TO ANY CLEANERS - GOOD SHOCK RESISTANCE and GOOD FASTLIGHTNESS.

The product is neutral and can be coloured by Toners or by the Tintometric System SPEEDY2, mixing manually the two components before application.

IDEAL USES

DAMASCATO is ideal to decorate interior walls. It allows to obtain very prestigious finishings with ancient effect. It also allows various decorative finishings, depending on the application method adopted.

TECHNICAL CHARACTERISTICS

SPECIFIC WEIGHT:

1,00 - 1,08 kg/l.

VISCOSITY :

6.000 - 15.000 cps at 23°C.

SPREAD RATE PER COAT:

100 g/m², depending on the desired decorative finishing.

APPEARANCE AND FINISH:

Matt appearance, smooth finish

VOC EMISSION LIMITS

(VOLATILE ORGANIC COMPOUNDS):

EU limit value of VOC (Directive 2004/42/EC) for these products (Cat.A/1;WB): 300 g/l (2007); 200 g/l (2010).

DAMASCATO contains less than 200 g/l of VOC.

WAY OF USE

PREPARATION OF THE SURFACE:

ON NEW WALLS: brush, fill holes or cracks and apply one coat of PRIMER UNIFORMANTE A.S. properly diluted.

After 3-4 hours apply 1-2 coats of FONDO PER DAMASCATO and after drying apply DAMASCATO finishing crisscrossing the brushstrokes on about 2 m² per time.

ON ALREADY PAINTED WALLS: remove all detached parts and then proceed as on new walls.

APPLICATION:

Apply DAMASCATO finishing using the appropriate brush. After 30 minutes smooth the product with the special flexible spatula, applying a slight pressure in order to obtain the desired decorative effect.

DILUTION:

Ready to use product, if necessity dilute with water.

DRYING AT 20°C AND 65% R.H.:

Dust free after about 2 hours, in depth after 24 hours. For complete drying in order to achieve the washing resistance wait at least 15 days.

ENVIRONMENTAL CONDITIONS:

The product can be applied at temperatures (of both the environment and/or the surface) between +5°C and +30°C.

WARNINGS:

Mix the product manually to avoid the flocculus breaking.

TOOLS CLEANING:

With water immediately after use.

SALES PACKAGINGS 2 x 2,5l - 2 x 5l - 6 x 1,25l.

AVAILABLE COLOURS: Colours chart.

CONSERVATION AND STORAGE:

Store the cans well sealed in a cool and dry place, far away from frost.

NOTES:

This document has been issued at the best of our technical and scientific expertise. Di Donato Spa does not take any responsibility for the results obtained when using this product, since the conditions and application procedures are not controllable by us. Therefore it is advisable to preliminary check the suitability of the product in accordance with the specific case.

