

PLAISIR

DECORATIVE SILK EFFECT FINISH

PRODUCT PROPERTIES

PLAISIR is a decorative finish for interiors with a low environmental impact, formulated with resins in aqueous emulsion, special pearlescent and specific additives which give the product the following characteristics: excellent water vapor permeability, good adhesion, good washability and ease of application.

The particular formulation gives a pleasant "soft to the touch" silk effect.

IDEAL USES

PLAISIR is suitable for interiors on masonry, plasterboard, cement and other wall surfaces.

PLAISIR is a finish that creates special effects on walls due to the different refractions of light and imparts a pleasing and delicate texture to the surface.

Ideal for classic or modern environments.

TECHNICAL CHARACTERISTICS

SPECIFIC WEIGHT: 1,25 - 1,35 kg/l.

VISCOSITY: paste product - slightly thixotropic.

SPREAD RATE PER COAT: 100 g/m², depending on the finish required.

VOLUME SOLIDS: 46 ± 1.

APPEARANCE AND FINISH: Satin and smooth appearance.

VOC EMISSION LIMITS (VOLATILE ORGANIC COMPOUNDS): EU limit value (Directive 2004/42/EC) for this product (cat. A/I ; BA): 300 g/l (2007) ; 200 g/l (2010).
PLAISIR contains less than 200 g/l di VOC.

WAY OF USE

SURFACE PREPARATION:

ON NEW SURFACES: Prime with a coat of PRIMER UNIFORMANTE appropriately diluted.

ON ALREADY PAINTED SURFACES: remove any dust, oil and/or grease or any loose material and then proceed as per new surfaces.

In both cases, apply a coat of washable ACRYLIC white as a base coat.

APPLICATION:

PLAISIR can be applied with a metal or plastic trowel with rounded corners.

Apply a first coat evenly. Leave to dry and then apply a second coat over an area of 2-3 m² at a time working the material to gain the desired texture.

Proceed with the application in the same way always keeping the trowel moist

The final result can be customised depending on the method of application.

DILUTION:

ready for use.

DRYING AT 20°C AND 65% R.H. :

Touch dry after 5-6 hours, Completely dry in approximately 24 hours.

TIME BETWEEN COATS:

Approximately 4 hours at 20° C.

ENVIRONMENTAL CONDITIONS:

Apply the product when the temperature of both the general environment and the support s between +5°C and +30°C.

TOOLS CLEANING:

With water immediately after use.

SALES PACKAGINGS: 8 kg – 24 kg.

AVAILABLE COLOURS: White.

CONSERVATION AND STORAGE:

The product will remain in good condition for at least 18 months if stored in a cool, dry frost free place.

NOTE:

This document has been prepared to the best of our scientific and technical knowledge.

Di Donato SpA does not assume any responsibility for the results obtained when using this product as the conditions and methods of application are various and are not controlled by us.

We therefore advise that for best results the product is pre-tested to assess its suitability for individual specific cases.

